



Dimensions

Model	A1	A2	A3	B	C(H6)	D	E	F	G max.	G min.	H	J	K	L max.	L1	M1	M2	N1
QJR08	215	212	264	98	170	133.4	M12	66	14.5	-1.5	20	98 (81)	5	M75×2	30	38	30.8	95
QJR10	254	251	312	119	220	171.4	M16	81	19.0	0	39	96	5	M90×2	45	42	39.0	110
QJR12	315	312	360	133	220(300)	171.4(235)	M16(M20)	106	23.0	0	42	121	6	M115×2	50	50	45.2	111

Model	N2	P	Q	R max.	R min.	S1	S2	T	U	V	W	X	Y	Z	α	β	γ
QJR08	85.0	25	34.0	20.4-44.4	16.7-40.7	35	28	7.25	14	M6×12	150	17	15	50	80	170	M8×15
QJR10	100.5	30	40.5	21.2-52.7	16.8-48.3	40	35	11.30	16	M8×15	190	23	-15	50	100	220	M8×15
QJR12	108.0	30	57.0	33.9-69.9	28.6-64.6	50	50	12.00	21	M8×15(M10×16)	190(260)	22(27)	-15(-20)	45(50)	130	280	M10×17

Dimensions in () are at QJR12 in case of replacement of BB212.

KITAGAWA

Machine Tool Accessories <http://www.mta.kiw.co.jp/>

KITAGAWA IRON WORKS CO., LTD.

77-1 Motomachi, Fuchu-shi, Hiroshima-pref. 726-8610, Japan

TEL +81 847-40-0526 FAX +81 847-45-8911

- Specifications and outside appearance are subject to change without notice due to ongoing research and development.
- The color of the actual product may be different from the catalogue's due to printing matters.
- Catalogue contents as of 2009.9
- The products herein are controlled under Japanese Foreign Exchange and Foreign Trade Control Act. In the event of importing and/or exporting the products, you are obliged to consult KITAGAWA as well as your government for the related regulation prior to any transaction.