

パワーチャック用ハードジョー把握範囲一覧 (ジョー型式をクリックすると各ジョーの寸法図を表示します。)

チャック	ジョー	3Dデータ	外径把握								内径把握				ハードジョー外径把握可動範囲
			A1	Fig.NO.	A2	Fig.NO.	A3	Fig.NO.	A4	Fig.NO.	B1	Fig.NO.	B2	Fig.NO.	ハードジョー内径把握可動範囲
B-204	HB04N1	Parasolid ㊦	---	---	15-19	11	76-80	11	---	---	---	---	---	---	15-19, 28-35, 42-49, 76-80, 103-110
		STEP ㊦	28-35	10	42-49	12	103-110	12	---	---	77-84	10	---	---	77-84
B-205	HB04N1	Parasolid ㊦	8-30	9	22-44	11	83-105	11	---	---	57-79	9	---	---	8-74, 83-105, 110-135
		STEP ㊦	35-60	10	49-74	12	110-135	12	---	---	84-109	10	---	---	57-79, 84-109
B-206	HB06A1	Parasolid ㊦	13-41	9	---	---	100-122	11	---	---	70-98	9	---	---	13-41, 52-83, 100-122, 133-164
		STEP ㊦	52-83	10	---	---	133-164	12	---	---	110-138	10	---	---	70-98, 110-138
B-206	HB06B1	Parasolid ㊦	17-39	5	38-56	5	18-46	7	44-72	7	131-153	5	142-169	5	17-111
		STEP ㊦	50-78	6	67-95	6	57-85	8	83-111	8	---	---	---	---	131-169
B-208	HB08A1	Parasolid ㊦	25-55	1	14-41	3	76-103	3	112-139	3	104-134	1	140-170	1	14-55, 59-106, 112-154, 157-190
		STEP ㊦	73-106	2	59-92	4	121-154	4	157-190	4	152-185	2	188-210	2	104-134, 140-185, 188-210
B-210	HB10A1	Parasolid ㊦	17-60	1	35-78	3	121-164	3	155-198	3	102-139	1	141-178	1	17-254
		STEP ㊦	77-120	2	95-138	4	181-224	4	215-254	4	162-199	2	201-238	2	102-139, 141-199, 201-238
B-212	HB12N1	Parasolid ㊦	42-104	9	---	---	172-237	11	---	---	133-195	9	---	---	42-164, 172-297
		STEP ㊦	102-164	10	---	---	232-297	12	---	---	193-255	10	---	---	133-255
B-215	HB15N1	Parasolid ㊦	42-116	1	33-83	3	171-221	3	225-275	3	157-232	1	211-285	1	33-221, 225-362
		STEP ㊦	126-200	2	96-170	4	234-308	4	288-362	4	241-316	2	295-369	2	157-369

